


Roller bearing NA6905-JTEKT - NA6905-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/na6905-jtekt>

Machined ring needle roller bearings ————— **Koyo**
F_w 29 – 37 mm

With inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. |
|--------------------------|----|----|----|-------------------------|------------------|--|--------------------|-------------|
| F _w | d | D | B | C _r | C _{10r} | Oil lub. | Without inner ring | |
| 30 | 25 | 42 | 30 | 40.1 | 60.7 | 15 000 | — | |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | |
| With inner ring | | | | Without inner ring | With inner ring | | | |
| NA6905 | | | | 0.3 | 0.112 | 0.162 | IRM253030 | |

[Note] 1) Limiting speeds of bearing number NA49..LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952482750 |
| Inside diameter | 25 mm |
| Outside diameter | 42 mm |
| Thickness | 30 mm |
| Weight | 162 g |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE