


Roller bearing 25NQI4425A-JTEKT - 25NQI4425A-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/25nqi4425a-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 ~ 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.		
F_w	d	D	B	C_r	C_{10}	Oil lub.	Without inner ring	Without inner ring	Without inner ring	
30	25	44	25	25.5	36.0	48.8	14 000	—	—	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.				
With inner ring				Without inner ring	With inner ring	Without inner ring		With inner ring		
25NQI4425A				27	42	0.3	—	0.161	—	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952482767
Inside diameter	25 mm
Outside diameter	44 mm
Thickness	25 mm
Weight	161 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE