


Roller bearing NA49-28R-JTEKT - NA49-28R-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/na49-28r-jtekt>

Machined ring needle roller bearings **Koyo**
F_w 29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No. Without inner ring
F _w	d	D	B	B ₁	C _r	C _{10r}	Oil lub.	Grease lub.		
32	28	45	17	—	0.3	25.0	33.8	14 000	—	
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring					d ₁ max.	D ₁ max.	r _a max.	Without inner ring	With inner ring	
NA49/28R					30	43	0.3	0.075	0.099	IRM283217

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952482828
Inside diameter	28 mm
Outside diameter	45 mm
Thickness	17 mm
Weight	99 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE