

## Roller bearing NQS32-22-JTEKT - NQS32-22-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/nqs32-22-jtekt>

Machined ring needle roller bearings ————— **Koyo**  
F<sub>w</sub> 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.		Without inner ring	
32	25	47	22	0.3	31.2	41.4	14 000	<b>NQS32/22</b>	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
	d <sub>a</sub> min.	D <sub>a</sub> max.	r <sub>a</sub> max.	0.123	0.167				
	27	45	0.3						

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952482835
Inside diameter	32 mm
Outside diameter	47 mm
Thickness	22 mm
Weight	123 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE