


Needle roller bearing NQI35-20-JTEKT - NQI35-20-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/nqi35-20-jtekt>

Machined ring needle roller bearings Koyo
F_W 29 ~ 37 mm

With inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. | |
|--------------------------|----|----|----|-------------------------|---------------------|------------------------------------|--|--------------------|--------------------|--|
| F _w | d | D | B | B ₁ | C _r | C _{0r} | Oil lub. | Without inner ring | Without inner ring | |
| 40 | 35 | 50 | 20 | — | 27.2 | 48.8 | 12 000 | — | — | |
| Mounting dimensions (mm) | | | | [Refer.] Mass (kg) | | [Refer.] Applicable inner ring No. | | | | |
| With inner ring | | | | d ₁ min. | D ₁ max. | r ₁ max. | Without inner ring | With inner ring | | |
| NQI35/20 | | | | 37 | 48 | 0.3 | 0.085 | 0.129 | | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952483047 |
| Inside diameter | 35 mm |
| Outside diameter | 50 mm |
| Thickness | 20 mm |
| Weight | 129 g |
| Packaging | 1 |
| Standard | No standard |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE