


## Roller bearing NQI38-30-JTEKT - NQI38-30-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/nqi38-30-jtekt>

### Machined ring needle roller bearings Koyo

$F_w$  29 ~ 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.		
$F_w$	d	D	B	$B_1$	$r$ (mm)	$C_r$	$C_{10}$	Oil lub.	Without inner ring	Without inner ring	
43	38	53	30	30	0.6	41.3	85.9	10 000	—	—	
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.				
With inner ring					Without inner ring	With inner ring					
					$d_a$ min.	$D_a$ max.	$r_a$ max.	—	0.205	—	—
					<b>NQI38/30</b>						

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952483191
Inside diameter	38 mm
Outside diameter	53 mm
Thickness	30 mm
Weight	205 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE