

Roller bearing RNA49-48R-JTEKT - RNA49-48R-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/rna49-48r-jtekt>

Machined ring needle roller bearings ————— **Koyo**
F_W 29 ~ 37 mm

Without inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. Without inner ring | |
|--------------------------|---|----|----|-------------------------|-----------------|--|--------------------|-----------------------------------|---------------------------|
| F _w | d | D | B | C _r | C ₁₀ | Oil lub. | Without inner ring | | |
| 55 | — | 70 | 22 | 46.9 | 76.5 | 8 300 | — | RNA49/48R | |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | | |
| With inner ring | | | | d _a | D _a | r _a | Without inner ring | With inner ring | Applicable inner ring No. |
| | | | | — | 66 | 0.6 | 0.174 | — | — |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952483481 |
| Inside diameter | 55 mm |
| Outside diameter | 70 mm |
| Thickness | 22 mm |
| Weight | 174 g |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE