


## Roller bearing NA4912-JTEKT - NA4912-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/na4912-jtekt>

### Machined ring needle roller bearings Koyo

$F_w$  29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)			Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No. Without inner ring
$F_w$	$d$	$D$	$B$	$B_1$	$C_r$	$C_{10}$	Oil lub.	Grease lub.		
68	60	85	25	1	45.8	93.3	8 900		—	
Mounting dimensions (mm)					Inner ring Mass (kg)		Outer ring Mass (kg)		Applicable inner ring No.	
					Without inner ring	With inner ring	Without inner ring	With inner ring		
<b>NA4912</b>					65	80	1	0.310	0.459	IRM00825

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952483733
Inside diameter	60 mm
Outside diameter	85 mm
Thickness	25 mm
Weight	459 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE