


## Roller bearing NA5914-JTEKT - NA5914-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/na5914-jtekt>

Machined ring needle roller bearings Koyo

$F_w$  29 – 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.		
$F_w$	$d$	$D$	$B$	$C_r$	$C_{10}$	Oil lub.	Without inner ring			
80	70	100	40	107.0	207.0	5 700	—			
				Mounting dimensions (mm)		(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
				With inner ring	Without inner ring	With inner ring	Without inner ring			
				$d_a$	$D_a$	$r_a$				
				max.	max.	max.				
				NA5914	75	95	1	0.615	0.973	IRM708040

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952483870
Inside diameter	70 mm
Inside diameter	2.756" inch
Outside diameter	100 mm
Outside diameter	3.937" inch
Thickness	40 mm
Thickness	1.575" inch
Weight	973 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE