

## Tapered roller bearing 30332-JTEKT - 30332-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/30332-jjtekt>

Boundary dimensions

Single row table:

Bearing No.	Boundary dimensions (mm)						Basic load ratings (kN)		Fatigue load limit (kN)	Limiting speed (min-1)
	d	D	B	r	r1 (max)	r1 (min)	C <sub>0</sub>	C <sub>0R</sub>	C <sub>0L</sub>	Grease lub.
30332J	160	340	75	5	4	1170	1220	142	1100	

Double row table:

Bearing No.	Boundary dimensions (mm)						Basic load ratings (kN)		Fatigue load limit (kN)	Limiting speed (min-1)
	d	D	B	r	r1 (max)	r1 (min)	C <sub>0</sub>	C <sub>0R</sub>	C <sub>0L</sub>	Grease lub.
40332	160	340	75	5	4	1170	1220	142	1100	
40332R	160	340	75	5	4	1170	1220	142	1100	
40332L	160	340	75	5	4	1170	1220	142	1100	
40332J	160	340	75	5	4	1170	1220	142	1100	
40332H	160	340	75	5	4	1170	1220	142	1100	
40332K	160	340	75	5	4	1170	1220	142	1100	
40332M	160	340	75	5	4	1170	1220	142	1100	
40332N	160	340	75	5	4	1170	1220	142	1100	
40332P	160	340	75	5	4	1170	1220	142	1100	
40332Q	160	340	75	5	4	1170	1220	142	1100	
40332R	160	340	75	5	4	1170	1220	142	1100	
40332S	160	340	75	5	4	1170	1220	142	1100	
40332T	160	340	75	5	4	1170	1220	142	1100	
40332U	160	340	75	5	4	1170	1220	142	1100	
40332V	160	340	75	5	4	1170	1220	142	1100	
40332W	160	340	75	5	4	1170	1220	142	1100	
40332X	160	340	75	5	4	1170	1220	142	1100	
40332Y	160	340	75	5	4	1170	1220	142	1100	
40332Z	160	340	75	5	4	1170	1220	142	1100	

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3616060628374
Inside diameter	160 mm
Outside diameter	340 mm
Thickness	75 mm
Limiting speed	1100 rpm
Dynamic load	1170 kN
Static load	1220 kN
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE