


Drawn cup roller bearing J-68-JTEKT - J-68-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/drawn-cup/j-68-jtekt>

Boundary dimensions



High series, with cage assembly

| Bearing No. | Boundary dimensions(mm) | | | | Basic load ratings(kN) | | Fatigue load limit(kN) | | Limiting speeds(min-1) | |
|-------------|-------------------------|--------|------|--------|------------------------|------|------------------------|-------------|------------------------|--|
| | Fw | D | C | Y(max) | Cr | Cor | Cu | Grease lub. | Oil lub. | |
| J-68 | 9.525 | 14.288 | 12.7 | 1.02 | 5.22 | 5.72 | 0.86 | 18000 | 27000 | |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3616060629821 |
| Inside diameter | 9.525 mm |
| Outside diameter | 14.288 mm |
| Thickness | 12.7 mm |
| Limiting speed | 18000 rpm |
| Dynamic load | 5.22 kN |
| Static load | 5.72 kN |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE