


Needle roller cage K24-28-17-H-JTEKT - K24-28-17-H-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/cage/k24-28-17-h-jtekt>

Boundary dimensions



Needle roller and cage assemblies

| Bearing No. | Boundary dimensions(mm) | | | Basic load ratings(kN) | | Fatigue load limit(kN) Cr | Limiting speed(min-1) | |
|-------------|-------------------------|----|----|------------------------|------|------------------------------|-----------------------|----------|
| | Fw | Fw | Bc | Cr | C0r | | Grease lub. | Oil lub. |
| K24X28X17H | 24 | 28 | 17 | 15.4 | 26.4 | 4.1 | 12000 | 18000 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3616060634092 |
| Inside diameter | 24 mm |
| Outside diameter | 28 mm |
| Thickness | 17 mm |
| Limiting speed | 12000 rpm |
| Dynamic load | 15.4 kN |
| Static load | 26.4 kN |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE