


Needle roller cage K25-31-17-H-JTEKT - K25-31-17-H-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/cage/k25-31-17-h-jtekt>

Boundary dimensions



Radial needle roller and cage assemblies

| Bearing No. | Boundary dimensions(mm) | | | Basic load ratings(kN) | | Fatigue load limit(kN) | Limiting speeds(min-1) | |
|-------------|-------------------------|----|----|------------------------|------|------------------------|------------------------|----------|
| | Fw | Ew | Bw | C1 | C0 | C0 | Grease lub. | Oil lub. |
| K25X31X17H | 25 | 31 | 17 | 19.7 | 27.8 | 4.35 | 12000 | 18000 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3616060634245 |
| Inside diameter | 25 mm |
| Inside diameter | 0.984" inch |
| Outside diameter | 31 mm |
| Outside diameter | 1.22" inch |
| Thickness | 17 mm |
| Thickness | 0.669" inch |
| Limiting speed | 12000 rpm |
| Dynamic load | 19.7 kN |
| Static load | 27.8 kN |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE