


Needle roller cage K30-44-26-H-JTEKT - K30-44-26-H-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/cage/k30-44-26-h-jtekt>

Boundary dimensions



Radial needle roller and cage assemblies

| Bearing No. | Boundary dimensions(mm) | | | Basic load ratings(kN) | | Fatigue load limit(kN) | Limiting speeds(min-1) | |
|-------------|-------------------------|----|----|------------------------|------|------------------------|------------------------|----------|
| | Pr | Er | Bc | Cr | Cor | Ce | Grease lub. | Oil lub. |
| K30X44X26H | 30 | 44 | 26 | 52.4 | 59.9 | 9.55 | 10000 | 16000 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3616060634719 |
| Inside diameter | 30 mm |
| Outside diameter | 44 mm |
| Thickness | 26 mm |
| Limiting speed | 10000 rpm |
| Dynamic load | 52.4 kN |
| Static load | 59.9 kN |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE