


Needle roller cage K48-54-19-H-JTEKT - K48-54-19-H-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/cage/k48-54-19-h-jtekt>

Boundary dimensions



Roller needle roller and cage assemblies

| Bearing No. | Boundary dimensions(mm) | | | Basic load ratings(kN) | | Fatigue load limit(kN) | Limiting speeds(min-1) | |
|-------------|-------------------------|----|----|------------------------|------|------------------------|------------------------|----------|
| | Fi | Fo | Bc | Ct | Cw | Cs | Grease lub. | Oil lub. |
| K48X54X19H | 48 | 54 | 19 | 30.9 | 61.2 | 9.85 | 5700 | 8800 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3616060635815 |
| Inside diameter | 48 mm |
| Outside diameter | 54 mm |
| Thickness | 19 mm |
| Limiting speed | 5700 rpm |
| Dynamic load | 30.9 kN |
| Static load | 61.2 kN |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE