


## Needle roller cage K80-88-25-FV1-JTEKT - K80-88-25-FV1-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/cage/k80-88-25-fv1-jtekt>

Boundary dimensions



Rating of needle roller and cage assemblies

| Bearing No.  | Boundary dimensions(mm) |    |    | Basic load ratings(kN) |     | Fatigue load | Limiting speed(min-1) |          |
|--------------|-------------------------|----|----|------------------------|-----|--------------|-----------------------|----------|
|              | Fw                      | Fv | Bc | Cv                     | Clr | Cu           | Gross lub.            | Oil lub. |
| K80X88X25FV1 | 80                      | 88 | 25 | 54                     | 121 | 19.2         | 3400                  | 5200     |

## PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | JTEKT         |
| N° Ean13         | 3616060636485 |
| Inside diameter  | 80 mm         |
| Outside diameter | 88 mm         |
| Thickness        | 25 mm         |
| Limiting speed   | 3400 rpm      |
| Dynamic load     | 54 kN         |
| Static load      | 121 kN        |
| Packaging        | 1             |

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE