


Drawn cup roller bearing BAM1016-IKO - BAM1016-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/drawn-cup/bam1016-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number												
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g				
15.875 ($\frac{5}{8}$)	—	—	—	—	—	—	—	BAM 1016	18.4	—	—		
Boundary dimensions		mm(inch)		Standard mounting dimensions				mm		Basic dynamic load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring
F_w	D	C	b_2	Shaft dia. h8	Housing bore dia. J7	Max.	Min.	Max.	Min.	N	N	rpm	
15.875 $\frac{1}{4}$	20.638 $\frac{3}{4}$	25.40(1.000)	1.3	15.875	15.864	20.650	20.629	12 300	20 800	25 000	IRB 716		

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952172927
Inside diameter	15.88 mm
Outside diameter	20.64 mm
Thickness	25.4 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE