

Drawn cup roller bearing BAM126-IKO - BAM126-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/drawn-cup/bam126-iko>

Shaft dia. mm (inch)	Identification number			Identification number			Mass (Ref.) g	Grease retained Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end		
19.050 (3/4)	—	—	—	—	—	BAM 126	11.7	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾	Assembled inner ring
F _w	D	C	Shaft dia. h6		Housing bore dia. J7		C	C ₀	N	N	rpm	—
19.050 7/8	25.400 1	9.52 .375	1.3	19.050 Max.	19.037 Min.	25.412 Max.	25.391 Min.	5 040	5 850	20 000	—	

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173047
Inside diameter	19.05 mm
Inside diameter	3/4" inch
Outside diameter	25.4 mm
Outside diameter	1" inch
Thickness	9.52 mm
Thickness	0.375" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE