


Drawn cup roller bearing BAM1310-IKO - BAM1310-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/drawn-cup/bam1310-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Standard			Closed end			Identification number			Grease retained Mass (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Mass (Ref.) g		
20.638 ($\frac{3}{16}$)	—	—	—	—	—	—	—	BAM 1310	20	—	—

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C	Shaft dia. h_6	Housing bore dia. J_7		C	C_0	rpm	IRB 910	
			Max. Min.	Max. Min.		N	N			
20.638 $\frac{3}{16}$	26.988 $1 \frac{1}{16}$	15.881 $\frac{5}{16}$	20.638 20.625	27.000 26.979		9 870	14 200	19 000	IRB 910	

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173061
Inside diameter	20.64 mm
Outside diameter	26.99 mm
Thickness	15.88 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE