


## Drawn cup roller bearing BAM138-IKO - BAM138-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/drawn-cup/bam138-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
<b>20.638</b> ( $\frac{3}{16}$ )	—	—	—	—	—	—	—	<b>BAM 138</b>	16.4	—	—
Boundary dimensions mm(inch)		Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring		
<i>F<sub>w</sub></i>	<i>D</i>	<i>C</i>	<i>B</i>	Shaft dia. <i>d</i>	Housing bore dia. <i>J7</i>	<i>C</i>	<i>C<sub>0</sub></i>	<i>n</i>	<i>IRB 98</i>		
20.638	26.988	12.70	5.00	1.3	20.638	20.625	27.000	26.979	7 170	9 450	19 000

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173122
Inside diameter	20.64 mm
Outside diameter	26.99 mm
Thickness	12.7 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE