


Drawn cup roller bearing BAM1422-IKO - BAM1422-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/drawn-cup/bam1422-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g				
	Standard	Mass (Ref.) g	Closed end														
22.225 (7/8)	---	---	---	---	---	---	---	---	---	---	---	---	---				
Boundary dimensions		mm(inch)		Standard mounting dimensions				mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾		Assembled inner ring	
F_w	D	C	h_6	Shaft dia.		Housing bore dia.		Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾		Assembled inner ring			
				Max.	Max.	Min.	Max.	Min.	N	N	rpm						
22.225	28.575	34.92	h6	22.225	22.212	28.587	28.566		24 100	45 700	18 000				IRB 1022		

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173177
Inside diameter	22.23 mm
Outside diameter	28.58 mm
Thickness	34.92 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE