


Drawn cup roller bearing BAM148-IKO - BAM148-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/drawn-cup/bam148-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
22.225 ($\frac{7}{8}$)	—	—	—	—	—	—	—	BAM 148	17.8	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic	Basic static	Allowable	Assembled
F_w	D	C	Shaft dia. ϕ		Housing bore dia. J_7		load rating C	load rating C_0	rotational speed ⁽¹⁾	inner ring
			Max.	Min.	Max.	Min.	N	N	rpm	
22.225	28.575	12.70	22.225	22.212	28.587	28.566	7 440	10 100	18 000	IRB 106

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173191
Inside diameter	22.23 mm
Outside diameter	28.58 mm
Thickness	12.7 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE