

## Drawn cup roller bearing BAM1510-IKO - BAM1510-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/drawn-cup/bam1510-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series

BAM BHAM

Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
<b>23.812</b> ( $\frac{9}{4}$ )	—	—	—	—	—	—	—	<b>BAM 1510</b>	<b>23</b>	—	—
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring	
<i>F<sub>w</sub></i>	<i>D</i>	<i>C</i>	<i>f</i> Max.	Shaft dia. h <sub>s</sub> Max.   Min.	Housing bore dia. J7 Max.   Min.	h <sub>7</sub> Max.   Min.	N	N	rpm	IRB 1110	
23.812   $\frac{9}{4}$	30.162   $1\frac{1}{8}$	15.88   $\frac{5}{8}$	2.8	23.812   23.799	30.176   30.151	11 000	17 100	16 000			

Note<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173207
Inside diameter	23.81 mm
Outside diameter	30.16 mm
Thickness	15.88 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE