

## Drawn cup roller bearing BAM158-IKO - BAM158-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/drawn-cup/bam158-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series

BAM BHAM

Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
<b>23.812</b> ( $\frac{9}{4}$ )	—	—	—	—	—	—	—	<b>BAM 158</b>	19	—	—
Boundary dimensions mm(inch)			Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed(*)	Assembled inner ring		
F <sub>w</sub>	D	C	h <sub>s</sub> Max.	h <sub>s</sub> Min.	Housing bore dia. J7 Max.	J7 Min.	N	N	rpm		
23.812   $\frac{9}{4}$	30.162   $1\frac{1}{8}$	12.70   500	2.8	23.812   23.799	30.176   30.151	8 000	11 400	16 000	—		

Note(\*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173221
Inside diameter	23.81 mm
Outside diameter	30.16 mm
Thickness	12.7 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE