


## Drawn cup roller bearing BAM1610-IKO - BAM1610-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/drawn-cup/bam1610-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
	BAM 1610												
25.400 (1)													
Boundary dimensions mm(inch)													
$F_w$	$D$	$C$	$t$	Shaft dia. mm		Housing bore dia. mm		Basic dynamic load rating C		Basic static load rating C <sub>0</sub>		Allowable rotational speed(*) rpm	
25.400	31.750	15.88	2.8	25.400	25.387	31.764	31.739	11 900	18 100	15 000			

Note(\*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173238
Inside diameter	25.4 mm
Outside diameter	31.75 mm
Thickness	15.88 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE