


Drawn cup roller bearing BAM166-IKO - BAM166-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/drawn-cup/bam166-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring	
	Standard	Mass (Ref.) g	Closed end					Mass (Ref.) g
25.400 (1)	—	—	—	BAM 166	16	—	—	
Boundary dimensions mm(inch)		Standard mounting dimensions mm						
<i>F_w</i>	<i>D</i>	<i>C</i>	Shaft dia. h _s	Housing bore dia. J7				
25.400	31.750	9.52	Max. Min.	Max. Min.	N	N	15 000	

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173283
Inside diameter	25.4 mm
Outside diameter	31.75 mm
Thickness	9.52 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE