


## Drawn cup roller bearing BAM1716-IKO - BAM1716-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/drawn-cup/bam1716-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained g	Mass (Ref.) g														
	BAM 1716																										
26.988 (1 1/8)																											
Boundary dimensions mm(inch)																											
F <sub>w</sub>			D			C			t			Shaft dia. h <sub>s</sub>		Housing bore dia. J7		Basic dynamic load rating C		Basic static load rating C <sub>0</sub>		Allowable rotational speed(*)		Assembled inner ring					
26.988   1 1/8			33.338   1 1/4			25.40   1.000			2.8			26.988   1 1/8		26.975   1 1/8		33.352   1 1/4		33.327		20 000		38 900		14 000		—	

Note(\*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173320
Inside diameter	26.99 mm
Outside diameter	33.34 mm
Thickness	25.4 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE