

Tapered roller bearing 30316-J2-SKF - 30316-J2-SKF

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/30316-j2-skf>

Dimensions d'encadrement			Charges de base		Vitesses de base		Désignation	
d	D	T	C	C ₀	Vitesse de référence	Vitesse limite	* Roulement SKF Explorer	
mm			kN		tr/min			
80	170	42,5	270	320	3000	4300	30316 J2	

Technical drawing showing dimensions: $t = 42,5$, $C = 33$, $r_{1,2min} = 3$, $B = 39$, $d = 80$, $D = 170$, $r_{3,4min} = 2,5$, $a = 53$, $d_1 = 120$, $C_{dyn} = 8$, $C_{stat} = 9,5$, $D_{dyn} = 153$, $D_{stat} = 148$, $d_{stat} = 100$, $d_{dyn} = 90$, $r_{1,2min} = 2,2$, $r_{3,4min} = 2,5$.

Coefficients de calcul:
 $\alpha = 0,25$
 $\beta = 1,2$
 $\gamma = 0,9$

PRODUCT FEATURES

Brand	SKF
N° Ean13	3663952026510
Inside diameter	80 mm
Outside diameter	170 mm
Thickness	42.5 mm
Weight	4185 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE