

Housed bearing accessorie YSPAG205-SKF - YSPAG205-SKF

<https://www.123bearing.co.uk/bearing-housing/housed-bearing/accessories/yspag205-skf>

| Dimensions d'encombrement | | | | Charges de base | | Vitesse limite | Désignation |
|---------------------------|----|----------------|----|-----------------|----------------------------|----------------|-------------|
| d | D | B ₁ | C | dynamique C | statique C ₀ | tr/min | |
| mm | | | | kN | | | |
| 25 | 52 | 33 | 15 | 14 | 7,8 | 1800 | YSPAG 205 |

Cili heraphato [mm] 25
 Coque de serrage recommandé [mm] 42
 Douille caoutchouc appropriée RS 205
 Coefficient de calcul f_g 14

Values for B₁ and a₁ before the grub screw is tightened
 (Sleeve and inner ring both in starting position)

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | SKF |
| N° Ean13 | 3663952232263 |
| Inside diameter | 25 mm |
| Outside diameter | 52 mm |
| Thickness | 33 mm |
| Tightening | Concentra |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE