

## Tapered roller bearing 30240J2-SKF - 30240J2-SKF

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/30240j2-skf>

Dimensions d'encombrement			Charges de base		Vitesses de base		Désignation
d	D	T	C	C <sub>0</sub>	Vitesse de référence	Vitesse limite	* Roulement SKF Explorer
mm			kN		tr/min		
200	360	64	792	1120	1300	1700	30240 J2

  

Technical drawing showing dimensions and coefficients of calculation for the tapered roller bearing 30240J2-SKF. The drawing includes the following dimensions: d = 200 mm, D = 360 mm, T = 64 mm, C = 40 mm, C<sub>max</sub> = 9 mm, C<sub>min</sub> = 16 mm, D<sub>max</sub> = 343 mm, D<sub>min</sub> = 315 mm, D<sub>max</sub> = 336 mm, D<sub>min</sub> = 300 mm, r<sub>1,ext</sub> = 5 mm, r<sub>2,ext</sub> = 4 mm, r<sub>1,int</sub> = 5 mm, r<sub>2,int</sub> = 4 mm, and a fillet radius of 0.58 mm. The coefficients of calculation are: e = 0.43, Y<sub>1</sub> = 1.4, and Y<sub>2</sub> = 0.8.

### PRODUCT FEATURES

Brand	SKF
N° Ean13	3663952236179
Inside diameter	200 mm
Outside diameter	360 mm
Thickness	64 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE