


## Roller bearing NCF2922CV-SKF - NCF2922CV-SKF

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/ncf2922cv-skf>

Dimensions d'encombrement			Charges de base		Vitesses de base		Désignation
d	D	B	dynamique C	statique C <sub>0</sub>	Vitesse de référence tr/min	Vitesse limite	
mm			kN				
110	150	24	134	220	1900	2400	NCF 2922 CV



Technical drawing showing dimensions and coefficients for the NCF2922CV roller bearing. Dimensions include: D = 150 mm, d = 110 mm, B = 24 mm, D<sub>1</sub> = 128 mm, E = 141.3 mm, f<sub>1</sub> = 2.3 mm, f<sub>2</sub> = 2.3 mm, r<sub>1</sub> = 1.1 mm, r<sub>2</sub> = 1.1 mm, r<sub>3</sub> = 1.5 mm, D<sub>2</sub> = 144 mm, D<sub>3</sub> = 144 mm, D<sub>4</sub> = 144 mm, D<sub>5</sub> = 118 mm, D<sub>6</sub> = 122 mm. Coefficients: k<sub>1</sub> = 0.2, e = 0.3, Y = 0.4.

### PRODUCT FEATURES

Brand	SKF
N° Ean13	7316572305607
Inside diameter	110 mm
Outside diameter	150 mm
Thickness	24 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE