

## Roller bearing NCF2944CV-SKF - NCF2944CV-SKF

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/ncf2944cv-skf>

Dimensions d'encombrement			Charges de base		Vitesses de base		Designation
d	D	B	dynamique C	statique C <sub>0</sub>	Vitesse de référence tr/min	Vitesse limite	
mm			kN				
220	300	48	550	1060	950	1200	NCF 2944 CV

  

The technical drawings show the bearing's geometry with the following dimensions and coefficients:

- Outer diameter (D): 300 mm
- Inner diameter (d): 220 mm
- Width (B): 48 mm
- Shoulder diameter (d<sub>1</sub>): 247 mm
- Shoulder diameter (d<sub>2</sub>): 289 mm
- Shoulder width (E): 205 mm
- Shoulder width (E<sub>1</sub>): 214 mm
- Shoulder width (E<sub>2</sub>): 231 mm
- Shoulder width (E<sub>3</sub>): 243 mm
- Shoulder width (E<sub>4</sub>): 251 mm
- Shoulder width (E<sub>5</sub>): 269 mm
- Shoulder width (E<sub>6</sub>): 289 mm
- Shoulder width (E<sub>7</sub>): 300 mm
- Shoulder width (E<sub>8</sub>): 300 mm
- Shoulder width (E<sub>9</sub>): 300 mm
- Shoulder width (E<sub>10</sub>): 300 mm
- Shoulder width (E<sub>11</sub>): 300 mm
- Shoulder width (E<sub>12</sub>): 300 mm
- Shoulder width (E<sub>13</sub>): 300 mm
- Shoulder width (E<sub>14</sub>): 300 mm
- Shoulder width (E<sub>15</sub>): 300 mm
- Shoulder width (E<sub>16</sub>): 300 mm
- Shoulder width (E<sub>17</sub>): 300 mm
- Shoulder width (E<sub>18</sub>): 300 mm
- Shoulder width (E<sub>19</sub>): 300 mm
- Shoulder width (E<sub>20</sub>): 300 mm
- Shoulder width (E<sub>21</sub>): 300 mm
- Shoulder width (E<sub>22</sub>): 300 mm
- Shoulder width (E<sub>23</sub>): 300 mm
- Shoulder width (E<sub>24</sub>): 300 mm
- Shoulder width (E<sub>25</sub>): 300 mm
- Shoulder width (E<sub>26</sub>): 300 mm
- Shoulder width (E<sub>27</sub>): 300 mm
- Shoulder width (E<sub>28</sub>): 300 mm
- Shoulder width (E<sub>29</sub>): 300 mm
- Shoulder width (E<sub>30</sub>): 300 mm
- Shoulder width (E<sub>31</sub>): 300 mm
- Shoulder width (E<sub>32</sub>): 300 mm
- Shoulder width (E<sub>33</sub>): 300 mm
- Shoulder width (E<sub>34</sub>): 300 mm
- Shoulder width (E<sub>35</sub>): 300 mm
- Shoulder width (E<sub>36</sub>): 300 mm
- Shoulder width (E<sub>37</sub>): 300 mm
- Shoulder width (E<sub>38</sub>): 300 mm
- Shoulder width (E<sub>39</sub>): 300 mm
- Shoulder width (E<sub>40</sub>): 300 mm
- Shoulder width (E<sub>41</sub>): 300 mm
- Shoulder width (E<sub>42</sub>): 300 mm
- Shoulder width (E<sub>43</sub>): 300 mm
- Shoulder width (E<sub>44</sub>): 300 mm
- Shoulder width (E<sub>45</sub>): 300 mm
- Shoulder width (E<sub>46</sub>): 300 mm
- Shoulder width (E<sub>47</sub>): 300 mm
- Shoulder width (E<sub>48</sub>): 300 mm
- Shoulder width (E<sub>49</sub>): 300 mm
- Shoulder width (E<sub>50</sub>): 300 mm
- Shoulder width (E<sub>51</sub>): 300 mm
- Shoulder width (E<sub>52</sub>): 300 mm
- Shoulder width (E<sub>53</sub>): 300 mm
- Shoulder width (E<sub>54</sub>): 300 mm
- Shoulder width (E<sub>55</sub>): 300 mm
- Shoulder width (E<sub>56</sub>): 300 mm
- Shoulder width (E<sub>57</sub>): 300 mm
- Shoulder width (E<sub>58</sub>): 300 mm
- Shoulder width (E<sub>59</sub>): 300 mm
- Shoulder width (E<sub>60</sub>): 300 mm
- Shoulder width (E<sub>61</sub>): 300 mm
- Shoulder width (E<sub>62</sub>): 300 mm
- Shoulder width (E<sub>63</sub>): 300 mm
- Shoulder width (E<sub>64</sub>): 300 mm
- Shoulder width (E<sub>65</sub>): 300 mm
- Shoulder width (E<sub>66</sub>): 300 mm
- Shoulder width (E<sub>67</sub>): 300 mm
- Shoulder width (E<sub>68</sub>): 300 mm
- Shoulder width (E<sub>69</sub>): 300 mm
- Shoulder width (E<sub>70</sub>): 300 mm
- Shoulder width (E<sub>71</sub>): 300 mm
- Shoulder width (E<sub>72</sub>): 300 mm
- Shoulder width (E<sub>73</sub>): 300 mm
- Shoulder width (E<sub>74</sub>): 300 mm
- Shoulder width (E<sub>75</sub>): 300 mm
- Shoulder width (E<sub>76</sub>): 300 mm
- Shoulder width (E<sub>77</sub>): 300 mm
- Shoulder width (E<sub>78</sub>): 300 mm
- Shoulder width (E<sub>79</sub>): 300 mm
- Shoulder width (E<sub>80</sub>): 300 mm
- Shoulder width (E<sub>81</sub>): 300 mm
- Shoulder width (E<sub>82</sub>): 300 mm
- Shoulder width (E<sub>83</sub>): 300 mm
- Shoulder width (E<sub>84</sub>): 300 mm
- Shoulder width (E<sub>85</sub>): 300 mm
- Shoulder width (E<sub>86</sub>): 300 mm
- Shoulder width (E<sub>87</sub>): 300 mm
- Shoulder width (E<sub>88</sub>): 300 mm
- Shoulder width (E<sub>89</sub>): 300 mm
- Shoulder width (E<sub>90</sub>): 300 mm
- Shoulder width (E<sub>91</sub>): 300 mm
- Shoulder width (E<sub>92</sub>): 300 mm
- Shoulder width (E<sub>93</sub>): 300 mm
- Shoulder width (E<sub>94</sub>): 300 mm
- Shoulder width (E<sub>95</sub>): 300 mm
- Shoulder width (E<sub>96</sub>): 300 mm
- Shoulder width (E<sub>97</sub>): 300 mm
- Shoulder width (E<sub>98</sub>): 300 mm
- Shoulder width (E<sub>99</sub>): 300 mm
- Shoulder width (E<sub>100</sub>): 300 mm

### PRODUCT FEATURES

Brand	SKF
N° Ean13	7316572382073
Inside diameter	220 mm
Outside diameter	300 mm
Thickness	48 mm
Limiting speed	1200 rpm
Weight	9888 g
Dynamic load	550 kN
Static load	1060 kN
Packaging	-
Standard	-

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE