

## Roller bearing NCF2956CV-SKF - NCF2956CV-SKF

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/ncf2956cv-skf>

Dimensions d'encombrement			Charges de base		Vitesse de base		Désignation
d	D	B	dynamique C	statique C <sub>0</sub>	Vitesse de référence tr/min	Vitesse limite	
mm			kN				
280	380	60	880	1730	700	800	NCF 2956 CV

  

Technical drawing showing dimensions and coefficients for the NCF2956CV roller bearing. The drawing includes a cross-section of the bearing with dimensions: d = 280 mm, D = 380 mm, B = 60 mm, r<sub>1,2max</sub> = 2.1 mm, r<sub>1,2min</sub> = 2.5 mm, E = 295.3 mm, E<sub>2</sub> = 247.5 mm, d<sub>1</sub> = 314 mm, and r = 3.5 mm. It also shows a detail of the roller with dimensions: r<sub>max</sub> = 399 mm, r<sub>min</sub> = 2 mm, D<sub>max</sub> = 369 mm, D<sub>min</sub> = 281 mm, and r<sub>max</sub> = 330 mm. Coefficients of calculation are listed as k<sub>r</sub> = 0.2, e = 0.3, and Y = 0.4.

### PRODUCT FEATURES

Brand	SKF
N° Ean13	7316572412930
Inside diameter	280 mm
Outside diameter	380 mm
Thickness	60 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE