

## TAPR Rod end SIQG20-ES-SKF - SIQG20-ES-SKF

<https://www.123bearing.co.uk/bearing-housing/rod-end/tapr/siqg20-es-skf>

Dimensions d'encombrement					Angle de déversement		Charges de base dynamique		Désignation	
d	d <sub>2</sub>	B	G	C <sub>1</sub>	h <sub>1</sub> ±	C		Embout à filetage à droite		
mm					degrés		kN			
20	50	20	M16x1,5	19	52	4	30	43	SIQG 20 ES	

  

Technical drawing showing dimensions and features of the SIQG20-ES-SKF rod end bearing. Dimensions include: d<sub>max</sub> 0,3; d<sub>2</sub> 20; B 20; C<sub>1</sub> 19; d<sub>max</sub> 50; h<sub>1</sub> 52; h<sub>1</sub> 4; d<sub>max</sub> 25,5; Ø M16x1,5; N<sub>max</sub> 18. Features include: Tétrances (r<sub>1</sub> 0,3; r<sub>2</sub> 0,16); Coefficient de pression spécifique; Constante de matière; Vis de cylindre M8; Couple de serrage 23.

### PRODUCT FEATURES

Brand	SKF
N° Ean13	7316577042804
Inside diameter	20 mm
Outside diameter	50 mm
Thickness	20 mm
Type	TAPR
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE