

## TAPR Rod end SIR80-ES-SKF - SIR80-ES-SKF

<https://www.123bearing.co.uk/bearing-housing/rod-end/tapr/sir80-es-skf>

Dimensions d'encombrement		Angle de déversement		Charges de base		Désignation			
d	d <sub>2</sub>	B	G	C <sub>1</sub>	h <sub>1</sub>	±	dynamique	statique	Embout à filetage à droite
mm	mm	mm	mm	mm	mm	degrés	kN	kg	
80	178	55	M50x2	60,5	170	5	400	560	SIR 80 ES

  

Technical drawing showing front and side views of the bearing. Dimensions include: d = 80 mm, d<sub>2</sub> = 178 mm, B = 55 mm, G = M50x2, C<sub>1</sub> = 60,5 mm, h<sub>1</sub> = 170 mm, and a taper angle of 5 degrees. The drawing also shows a cross-section of the bearing housing with dimensions: d<sub>max</sub> = 178 mm, d<sub>min</sub> = 80 mm, and a thickness of 55 mm. The bearing housing has a bore diameter of 80 mm and a bore length of 105 mm. The bearing housing has a bore diameter of 80 mm and a bore length of 105 mm. The bearing housing has a bore diameter of 80 mm and a bore length of 105 mm.

Tolerances:  
d<sub>2</sub> H7  
h<sub>1</sub> -

Coefficient de pression spécifique:  
185

Constante de matière:  
185

Vis de cylindre:  
M20

Couple de serrage:  
195

### PRODUCT FEATURES

Brand	SKF
N° Ean13	7316577003690
Inside diameter	80 mm
Outside diameter	178 mm
Thickness	55 mm
Type	TAPR
Weight	13000 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE