


## Tapered roller bearing 26131-26283-TIMKEN - 26131-26283-TIMKEN

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/26131-26283-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



| Bearing Dimensions |        |         | Load Ratings                             |                            |  |   |                          |       | Part Number |       |
|--------------------|--------|---------|--|----------------------------|--|---|--------------------------|-------|-------------|-------|
| Bore d             | O.D. D | Width B | Dynamic <sup>(1)</sup><br>C <sub>1</sub> | Factor <sup>(2)</sup><br>e | Dynamic <sup>(1)</sup><br>C <sub>2</sub> | Factor <sup>(2)</sup><br>e <sub>2</sub> | Static<br>C <sub>0</sub> | Inner | Outer       |       |
| mm                 | mm     | mm      | N  |                            | N  |   | N                        |       |             |       |
| 33.337             | 72.000 | 19.000  | 6900                                     | 1.67                       | 19100                                    | 11900                                   | 1.62                     | 69300 | 26131       | 26283 |
| 1.3125             | 2.8348 | 0.7480  | 15700                                    |                            | 4860                                     | 2500                                    |                          | 13580 |             |       |

| Bearing Dimensions |        |                          |  |                                      |  |                                      |                               |                               |                | Geometry Factors |                |      | Bearing Weight |      |
|--------------------|--------|--------------------------|--|--------------------------------------|--|--------------------------------------|-------------------------------|-------------------------------|----------------|------------------|----------------|------|----------------|------|
| Width              |        | Shaft                    |  | Housing                              |  | Cage                                 |                               |                               |                |                  |                |      |                |      |
| B                  | C      | ER. Dr. r <sup>(1)</sup> | Max Shaft Fillet Radius R <sup>(1)</sup> | Backing Shoulder Dia. d <sub>s</sub> | Max Housing Fillet Radius r <sup>(2)</sup> | Backing Shoulder Dia. D <sub>s</sub> | A <sub>1</sub> <sup>(3)</sup> | A <sub>2</sub> <sup>(3)</sup> | G <sub>1</sub> | G <sub>2</sub>   | C <sub>3</sub> |      |                |      |
| mm                 | mm     | mm                       | mm                                       | mm                                   | mm   | mm                                   | mm                            | mm                            |                |                  |                | kg   |                |      |
| 19.023             | 15.875 | -4.1                     | 3.5                                      | 38.5                                 | 44.5                                       | 1.5                                  | 85.9                          | 62.8                          | 8.5            | 1.1              | 16.1           | 10.1 | 0.9030         | 0.35 |
| 0.7493             | 0.6250 | -0.16                    | 0.14                                     | 1.52                                 | 1.75                                       | 0.06                                 | 2.56                          | 2.44                          | 0.32           | 0.05             |                |      |                | 0.79 |

### PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | TIMKEN        |
| N° Ean13         | 3663952310770 |
| Inside diameter  | 33.34 mm      |
| Outside diameter | 72 mm         |
| Thickness        | 19 mm         |
| Packaging        | 1             |

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE